

SCOOP DOUBLE-SILVERBACK

TECHNICAL SPECIFICATION

- » FRAME 26" Butted 6061 Aluminium, Tapered 1-1/8" – 1.5" headtube, 190mm QR Dropouts, 100mm BB width
- » SIZES S15",M17",L 19"
- » FORK Rigid Fork 26", Aluminium,Tapered steerer, Post mounts for Disc brake, 9mm QR Dropouts
- » RIMS Sunringlé Mulefut 80 SL, 32H, Tubeless Ready, Black
- » HUBS REAR Modus, 6-Bolt Disc Mount, Adjustable cup and cone angular contact bearings, Cassette, 190mm QR Axle Black; Front: Modus, 6-Bolt Disc Mount, Adjustable cup and cone angular contact bearings, 150mm QR Axle, Black
- » TYRES Maxxis Mammoth, 26" x 4.0, EXO Sidewall, Foldable, 120TPI, Black
- » STEM Sector Box, S/M/L: 60mm, 6° x 31.8mm, black
- » HANDLEBAR Sector Plane, W: 720mm; Back Sweep: 9° Up Sweep 5°; 15mm Rise; 31.8mm; 6061 Butted Oversized
- » SEATPOST Sector Level, Alloy, 31.6mm, S: 350mm; M: 400mm, Black
- » SADDLE Sector, Cr-Mo Rails, Light Foam Padding
- » BRAKE SET Shimano BL/BR-M615 Open Hydraulic System, Rotors Front: 180mm; Rear: 160mm, 6-Bolt, Black
- » SHIFTERS Shimano Deore SL-M610, 2x10 Trigger, Black
- » FRONT DERAILLEUR SRAM X5, Double, High Direct Mount, Black
- » REAR DERAILLEUR Shimano SLX RD-675 Shadow Plus, Long Cage, 10 Speed
- » CASSETTE Shimano CS-HG50, 10 Speed, 11-36T, Silver
- » CRANKSET Race Face Ride, Fat Bike Specific, 36/22T, L: 175mm ALL SIZES, Black
- » BOTTOM BRACKET Race Face, BSA Hydraulic Disc Shimano

